

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A device comprising:
a substrate;
at least ~~one~~ two active components formed on a top surface of the substrate;
at least one non-active region separating the active components;
a first laminate over the top surface of the substrate, encapsulating at least the active components; and
at least one support posts in the non-active regions of said device, providing support for said first laminate.
2. (Currently Amended) The device of claim 1 wherein the active components comprises ~~an~~ organic light emitting diode devices.
3. (Currently Amended) The device of claim 2 wherein the substrate supports the active components.
4. (Previously presented) The device of claim 3 wherein the substrate comprises a flexible substrate.
5. (Previously presented) The device of claim 4 wherein the substrate comprises a substrate material selected from a group of materials consisting of polymer, glass, ceramic, or semiconductor material.

6. (Previously presented) The device of claim 3 wherein the substrate comprises a transparent substrate.

7. (Previously presented) The device of claim 6 wherein the substrate is selected from a group of materials consisting of polymer or glass.

8. (Previously presented) The device of claim 3 wherein the substrate comprises a flexible transparent substrate.

9. (Previously presented) The device of claim 8 wherein the substrate comprises a material selected from a polymer or glass.

10. (Currently Amended) The device of claim 1 wherein the substrate supports the active components.

11. (Previously presented) The device of claim 10 wherein the substrate comprises a flexible substrate.

12. (Previously presented) The device of claim 11 wherein the substrate material is selected from a group of materials consisting of polymer, glass, ceramic, or semiconductor material.

13. (Previously presented) The device of claim 10 wherein the substrate comprises a transparent substrate.

14. (Previously presented) The device of claim 13 wherein the substrate material is selected from a group of materials consisting of polymer or glass.

15. (Previously presented) The device of claim 10 wherein the substrate comprises a flexible transparent substrate.

16. (Previously presented) The device of claim 15 wherein the substrate comprises a material selected from a polymer or glass.

17. (Currently Amended) The device of claim 13 or 14 further ~~comprises~~ comprising a second laminate on a bottom surface of the substrate, wherein the second laminate comprises a transparent laminate.

18. (Previously presented) The device of claim 17 wherein the first and second laminates comprise:

a laminate substrate; and

a sealant on a surface of the laminate substrate that contacts the device.

19. (Previously presented) The device of claim 18 wherein the laminate substrate comprises a material having a sufficient thermal stability to maintain mechanical integrity during the laminating process.

20. (Previously presented) The device of claim 19 wherein the laminate substrate comprises a plastic material.

21. (Previously presented) The device of claim 20 wherein the plastic laminate substrate is selected from poly (ethylene terephthalate), poly (butylene terephthalate), poly (entylene naphthalate), polycarbonate, polyimides, polysulfones, poly (p-phenylene ether sulfone), polyethylene, polypropylene, poly(vinyl chloride), polystyrene, or poly (methyl methyleacrylate).

22. (Previously presented) The device of claim 21 wherein the sealant comprises an activation temperature which causes the sealant to flow to ensure sealing between the laminate substrate and the device.

23. (Previously presented) The device of claim 22 wherein the activation temperature is between 80°C and 140°C.

24. (Previously presented) The device of claim 23 wherein the first and second laminates comprise a barrier layer, wherein the barrier layer inhibits the diffusion of air or moisture.

25. (Previously presented) The device of claim 24 wherein the barrier layer comprises a material selected from a group consisting of a metallic or a dielectric material.

26. (Previously presented) The device of claim 25 wherein the metallic material comprises copper or aluminum and the dielectric material comprises silicon monoxide, silicon oxide, silicon dioxide, silicon nitride (Si_2N_4), or a metal oxide.

27. (Previously presented) The device of claim 26 wherein the sealant comprises an activation temperature which causes the sealant to flow to ensure sealing between the laminate substrate and the device.

28. (Previously presented) The device of claim 27 wherein the activation temperature is between 80°C and 140°C.

29. (Previously presented) The device of claim 18 wherein the first and second laminates comprise a barrier layer on the laminate, the barrier layer inhibits the diffusion of air or moisture.

30. (Previously presented) The device of claim 29 wherein the barrier layer comprises a material selected from a group consisting of a metallic or a dielectric material.

31. (Currently Amended) The device of claim 10 further ~~comprises~~ comprising a second laminate on a bottom surface of the substrate.

32. (Previously presented) The device of claim 31 wherein said first and second laminates comprise:

a laminate substrate; and

a sealant on a surface of the laminate substrate that contacts the device.

33. (Previously presented) The device of claim 32 wherein the laminate substrate comprises a material having a sufficient thermal stability to maintain mechanical integrity during the laminating process.

34. (Previously presented) The device of claim 33 wherein the laminate substrate comprises a plastic material.

35. (Previously presented) The device of claim 34 wherein the plastic laminate substrate is selected from poly (ethylene terephthalate), poly (butylene terephthalate), poly (enthylen naphthalate), polycarbonate, polyimides, polysulfones, poly (p-phenylene ether sulfone), polyethylene, polypropylene, poly (vinyl chloride), polystyrene, or poly(methyl methyleacrylate).

36. (Previously presented) The device of claim 35 wherein the sealant comprises an activation temperature which causes the sealant to flow to ensure sealing between the laminate substrate and the device.

37. (Previously presented) The device of claim 36 wherein the activation temperature is between temperatures of 80°C and 140°C.

38. (Previously presented) The device of claim 37 wherein the first and second laminates comprise a barrier layer on the laminate, the barrier layer inhibits the diffusion of air or moisture.

39. (Previously presented) The device of claim 38 wherein the barrier layer comprises a material selected from a group consisting of a metallic or a dielectric material.

40. (Previously presented) The device of claim 39 wherein the metallic material comprises copper or aluminum and the dielectric material comprises silicon monoxide, silicon oxide, silicon dioxide, silicon nitride (Si_2N_4), or a metal oxide.

41. (Currently Amended) The device of claim 32 wherein the sealant comprises an activation temperature which causes the sealant to flow to ensure good sealing between the laminate substrate and the device.

42. (Previously presented) The device of claim 41 wherein the activation temperature is between temperatures of 80°C and 140°C.

43. (Previously presented) The device of claim 32 wherein the first and second laminates comprise a barrier layer on the laminate, the barrier layer inhibits the diffusion of air or moisture.

44. (Previously presented) The device of claim 43 wherein the barrier layer comprises a material selected from a group consisting of a metallic or a dielectric material.

45. (Previously presented) The device of claim 2 wherein the first laminate comprises:

a laminate substrate; and

a sealant on a surface of the laminate substrate that contacts the device.

46. (Previously presented) The device of claim 45 wherein the laminate substrate comprises a material having a sufficient thermal stability to maintain mechanical integrity during the laminating process.

47. (Previously presented) The device of claim 46 wherein the sealant comprises an activation temperature which causes the sealant to flow to ensure sealing between the laminate substrate and the device.

48. (Previously presented) The device of claim 47 wherein the first laminate comprises a barrier layer on the laminate, the barrier layer inhibits the diffusion of air or moisture.

49. (Previously presented) The device of claim 45 wherein the sealant comprises an activation temperature which causes the sealant to flow to ensure sealing between the laminate and the device.

50. (Previously presented) The device of claim 45 wherein the first laminate comprises a barrier layer on the laminate, the barrier layer inhibits the diffusion of air or moisture.

51.-85. (Cancelled)

86. (Currently Amended) The device of claim 1 wherein the at least one support posts comprises directly or indirectly photopatternable material.

87. (Previously presented) The device of claim 86 wherein the photopatternable material is a directly photopatternable material selected from a group consisting of photosensitive polyimide, photosensitive polybenzoxazole, photoresists, photoresists based on novolac systems or dry film resist materials.

88. (Previously presented) The device of claim 86 wherein the indirectly photopatternable material is selected from the group consisting of spin-on glass, polyimide, polybenzoxazole, polyglutarimide, benzocyclobutene, polymers, polyethylene, polystyrene, polystyrene, polypropylene, silicon dioxide, silicon nitride or aluminum oxide.

89. (Currently Amended) The device of claim 86 wherein the at least one support posts comprises a multi-layer architecture having at least first and second support layers.

90. (Currently Amended) The device of claim 87 wherein the at least one support posts comprises a multi-layer architecture having at least first and second support layers.

91. (Currently Amended) The device of claim 88 wherein the first support layer comprises a dielectric material to provide electrical isolation for the active components.

92. (Currently Amended) The device of claim 89 wherein the first support layer comprises a dielectric material to provide electrical isolation for the active components.

93. (Previously presented) The device of claim 89 wherein the first and second support layers comprise directly or indirectly photopatternable material.

94. (Cancelled)

95. (New) The device of claim 1, wherein:
a cavity between said first laminate and said active components is present; and
the at least one support post supports areas of said first laminate that is arranged above the cavity.

96. (New) The device of claim 1, wherein:
additional support posts are present in the periphery of the device, surrounding the active components.

97. (New) The device of claim 1, wherein:
a cavity is between said first laminate and said active components;

the height of the support post is greater than the height of the active components;
and
the first laminate spans the cavity.

98. (New) The device of claim 1, wherein:
the at least one support post prevents the first laminate from contacting the active components.

99. (New) A device comprising:
a substrate,
at least one active component formed on a top surface of the substrate,
a first laminate over the top surface of the substrate, encapsulating at least the active component, wherein the laminate is a sheet of uniform thickness, and
at least one support post in a non-active region of said device, providing support for said first laminate.

100. (New) The device of claim 99, further comprising:
a second active component,
at least one non-active region separating the first and second active components,
where the non-active region includes a region on the substrate where two electrodes do not intersect.